

AVIATION

The Oldest American Aeronautical Magazine

JUNE 1, 1925

Issued Weekly

PRICE 10 CENTS



A.C.I.D.N.A. three-engined Caudron at Angora

VOLUME
XVIII

SPECIAL FEATURES

NUMBER
22

THE DOUGLAS TRANSPORT

THE MOREHOUSE LIGHT PLANE ENGINE

NATIONAL AIR TRANSPORT, INC., FORMED

GARDNER PUBLISHING CO., INC.

HIGHLAND, N. Y.

225 FOURTH AVENUE, NEW YORK


Entered as Second-Class Matter, Nov. 22, 1920, at the Post Office at Highland, N. Y.
under Act of March 3, 1879.

*Ten Years of Packard Pioneering in Aircraft Motor Development
1915-1925*

Performance!



The Winning Airplane
It's engine 320-3, the Corps Observation plane 5000. Standard data is: 1100 h.p., 1400 rpm, 1000 ft. torque, 1000 ft. max. load, 1000 ft. maximum take-off and two men.



The Winning Motor
The Packard 18-1500 which powered the winning observation plane and second place. This engine has a bore of 4.125 in. and a stroke of 5.125 in. It has a displacement of 150 cu. in. & 12 p.

AFTER all is said and done, it is performance that counts in an aircraft engine. Planes and motors were given stiff performance tests in an Army Air Service competition for Corps Observation plane held recently at McCook Field. Airplane manufacturers were allowed to choose any engine for their entries. The two that selected the new 500 horse power Packard motor finished first and second in a crowded field.

PACKARD MOTOR CAR COMPANY

Detroit, Michigan

Ask The Man Who Owns One

Please Write to Advertisers. Please Mention AVIATION

JUN. 1, 1926

AVIATION

Published every Monday

CONTENTS

Editorial	587	Preparing the Night Airway	684
No Civil Air Transport Organized	588	The Douglas Transport	685
All Aviation Safety Code Completed	589	Airline Meeting	687
St. Louis-Bethelton Electrical Co. Formed	590	Aeronautic Graduate Recently Flew	687
Characteristics of a Single-Float Seaplane During Take-Off	591	Japanese Flight	687
To Amsterdam Expeditia	592	The Naval Air Battle of the Pacific	688
The Monocoupe Light Plane Engine	593	Light Planes and Gliders	689
Bi-Signed Characteristics of Airfields	595	Airports and Airways	690
United States Air Forces	596	United States Air Forces	692

GARDNER PUBLISHING COMPANY, Inc., Publishers

GENERAL AND EDITORIAL ROOMS 220 FOURTH AVENUE, NEW YORK

CABLE ADDRESS: AEROMIC

Publishing Office

HIGHLAND, N. Y.

Subscription price: Four dollars per year. Canada, five dollars. Foreign, six dollars. Single copies ten cents. Post number 35 cents. Copyright 1926, by the Gardner Publishing Company.

Entered every Month. Form 6000 tax dues previously
Entered as second-class matter Nov. 20, 1925, at the
Post Office at Highland, N. Y., under act of March
3, 1879.

ACCLES & POLLOCK, LTD.

OLDbury, BIRMINGHAM, ENGLAND

Specialists in Airplane Tubing and Tube Manipulation
Over 900 Different Sections

Oval and Streamline Sections in All Sizes and Gauges

Suppliers to the British Air Ministry, to all British
airplane manufacturers and to European governments

Write Us for Catalog of Sections and Send in Your Specifications

JONAS B. OGLAEND, INC.
15 MOORE STREET, NEW YORK

U.S.A. Representatives for Accles & Pollock, Ltd.

Please Write to Advertisers. Please Mention AVIATION



WILLIAM GIBSON, a
young Negro boy, was born
in the State of Ohio. His parents
are deceased. He has been
living with his mother since
the time of her marriage, and makes
his home with her. He is now
about twelve years of age.

THE EXCELLENT SERVICE

WRIGHT WHIRLWIND ENGINES ARE GIVING THE U.S. NAVY
HAS MADE THEM KNOWN THROUGHOUT THE WORLD

WRIGTH Whirlwind J-4, 200 H.P. Air-Cooled Engines have been selected by the Navies or Air Services of five countries in North and South America in addition to the U.S. Navy.

One of the recent important purchases and not the most important commercial aerostats—is the one Wright Whirlwind bought by the Huff-Daland Dusters, Inc., of Macon, Georgia, who have taken large acreage contracts for orchard and bellflower dusting.



WRIGHT AERONAUTICAL CORPORATION
Form W-112-A

WRIGHT WHIRLWIND J-4 AIR-COOLED ENGINE

L. D. DUNN ~~PRESIDENT~~
Geo. D. DUNN ~~VICE PRESIDENT~~
L. B. WALTER ~~TREASURER~~
CHESTER THOMAS ~~WITNESS~~

AVIATION

Editorial Board

DONALD W. McGLYNN
Editor
VINCENZO E. CLARK
EDWARD P. WALKER
RALPH H. UPTON
EDWARD T. ALLIN
Associate Editors

VOL. XXVII

JUNE 1, 1925

No. 12

A Welcome Newcomer

A NOTABLE addition to the history of American aviation was made this week when the National Air Transport flying company was reorganized. Heretofore, the three agencies which have been essential to the success of airlines have been lacking in some measure. The first of course is ample financial backing. Equally necessary is experienced management. While these two basic needs have available, the third essential to success is the race of modern and efficient aircraft. The new company appears to have all three of these essential factors.

The last item concerned the enterprise cost component of capital required for the extension of air transport services. Col Paul Headlam has at his command the experience and financial management that could be found nowhere in the world. And what is of even greater importance is planned to come shortly that nobody the least interested in aeroplane and poster planes as well as the transport industry can be unaware. With these statements available the probability of aeroplanes making money in transports abroad is at last in its first real low in the world.

Very early the new company is planning to carry only
air and express. Not a word has been said about pas-
senger. By taking the course there can be minimized the
greatest change to the new line. A strike on a pas-
senger train is a blow to revenue that is very difficult to
reverse. To the carrying of packages faster than any other

and new houses will be added the advantages of night or stock or refrigerated when in competition with night car service. No doubt, the insurance list of capitalists and stockholders who are interested in the new transport group will command the greatest respect from the business end. Confidence of this kind is needed when industry has made up its mind to test it with extensive trials of packages in the car. In securing traffic this closest will be the greatest assistance.

Why 200 Hz. for Training?

THERE are certain systems connected with flying and motor aviation but one of the greatest is the use of three planes, with engines developing from 150 to 260 h.p. There are those who argue that to really get the best of a plane one must learn to fly in a machine that is underpowered.

others claim that our team has an extremely, impressive engine with lots of reserve power and speed. Both schools I thought have their merit but whatever was out at that time to the point of this interest as either kind of machine to be built around an engine of less than 500 hp. The "Moth" is underpowered, but there has been a tremendous change in aerodynamics and in the knowledge of how to estimate since the J5 was first designed. Also a modern engine of 380 hp would weigh considerably less than the old G.K. It is almost indisputable that a two-seater of this weight has plenty of reserve power and speed. As far as a three-seater commercial planes with their XG engines there is plenty of reserve and the DeHavilland "Moth" with a 500-hp engine seems to be able to do all the things which may arise of mock combat however we are able to do.

Willis boasts the original cost of planes rises directly with their weight and the cost of engines rises with their horsepower. The operating and maintenance of planes also depends on their size so that it is safe to say that for the same amount of money, a considerably greater amount of flying can be done with 100 kg. planes than with 200 kg. planes. In short, while the air force President Coolidge is pushing economy and the Army and Navy are developing a reserve of certain pilots, both branches are designing and buying small training planes of continuously larger power planes which are more expensive to build and will increase considerably the cost of training new pilots or of maintaining reserves in a good flying condition.

Misplaced Economy

THE Army has a large surplus of Liberty engines more than it can use in years of peacetime service. These engines have a welded steel water jacket and the fact that these were originally made two tons is probably the most serious defect of the Liberty engine. Even with the most careful storage these valves will rust through and it is almost impossible to reassemble the jacket so as to hold a very cylinder. With the most handleable mixture of compressed air and steam the Liberty engine for years to come the Army has used the expedient of buffeting air cooled cylinders for the Liberty engine. The necessary experimental work has been going on at McCook Field for some time and the English engine has been tested out quite successfully. However, even now men in charge of the work admit that air cooled cylinders will not bring the Liberty engine up to the standard of modern aeroplane engines. It seems rather straightforward to suggest to the Army to use parts of engines which are otherwise especially when that work is expensive and the spending of an equal amount would naturally help in the development of another modern surplus engine.

The Morehouse Light Plane Engine

By HAROLD E. MOREHOUSE

Lester Drapko (Braeburn, McCook Field)

This engine, which will be known as the Model M-5, has been designed and built to conform to the N.A.A. contest requirements for light plane engines. In the design of this engine, particular attention has been paid to the weight of the engine, the strength of the engine, the reliability of the engine, the cost of the engine, and the cost of maintenance. The engine has been kept as light as possible, consistent with the necessary requirements of such an engine, and, while it is admitted that an engine of even lighter weight and of higher output could possibly be built at some extra capacity, it has been the aim of the designer to produce an engine which will have new and unique features and one that would give a conservative output with the maximum possible degree of dependability. The writer wishes it understood that it represents only Milwaukee engine with which he is connected in any way.

Tested at McCook

The first engine was submitted to McCook Field for cold test work, and the accompanying curve shows the results obtained. The photographs show the general arrangement of the engine quite clearly, and the overall dimensions are shown by the installation drawing. The engine has been designed so that a propeller reduction gear can be added when desired. The gear arrangement given is now being used by Thomas & Farness of Boston, Mass., who are engaged in research and development of aircraft propellers. The self-adjacent 34 lb. is the weight of the engine and will have a reduction gear of 2.25:1.

The Morehouse 56 cu in engine is a two cylinder opposed four cycle air cooled type having a bore of 3.750 in. and a stroke of 3.689 in. The compression ratio is 5.0 : 1. The engine is rated at 35 hp and 3500 normal r.p.m. Weight complete, as shown in photograph, 88 lb (dry).

Following automobile practice, ample large plain bearings are used throughout the engine; together with a full pressure oiling system in all bearings, means being provided to remove


late the oil pressure by adjustment.

The cylinder is a one-piece aluminum casting, tapered at both ends, as shown in Figure 1, which is assembled. The cylinders are attached to the case holding down flanges about half way up the base, their location being made as the cylinders by one at the flange and one at the mid of the barrel. The main bearing supports are located directly under the cylinder, in which they are ground and free from vibration when in operation. This mid. at to cool the lower half of the cylinder, is returned to by negative passages. The carburetor, which is placed above the cylinder, is mounted on the cylinder. The cylinder has a bore of 2.500 inches, and has two 100 deg. conical threads of S.A.E. 7046 steel. Nuts of large diameter are used in order to keep the cylinder as a minimum.

Perchlorate Uptake

Forged aluminum connecting rods have short, a loose piston pin bushings and removable bolted steel shells at the lower end. The flat head aluminum pistons are 7-1/8" long and have face 0.035 in. wide "Teebird" rings, three above the piston pin and one at the center of the bottom. The piston rings have beveled end planks and are free to float in both directions.

The cylinders are of cast iron having integral cooling fins. There are two trapezoid shaped "Ricci" cooling curves which per cylinder measure diametrically in the head having 50 deg each & 0.325 in. wide. The ports measure 1.075 in. in the side and




Jan 1, 1905


AVIATION

the valve lift is 6.375 in. The cylinders are provided with separate valve guide bushings to permit of replacement of the valves without removing the cylinder heads. The valves are operated by push rods and rocker arms, the rockers being provided at the push rod end and with means for adjusting the tappet clearance, and a plater at the valve end. The push rods are sufficiently recessed in these sockets that they cannot come out in flight. The rockers are supported by saddle and brackets which hold the cylinder by a single

Vapors are provided by a Scientific Magnetic Evaporating single vaporizing tube system. A combination thermometer and filter is mounted on the top of the cracking vessel, the thermometer being provided with a flange to which a tube may be attached, leading out of the oven to carry away any oil or vapors.



Plant and tree visitors of the *Musgrave Forest*



Power and fuel consumption curves of the Mitsubishi 6G73

High Speed Characteristics of Airfoils

• 100 •

Time can now measure the turning gear train, the crankshaft gear driving an after-shuttle, above the mainshaft, engaged with a sleeve which serves as the intermediate drive. The mainshaft has a drive from the after shaft at one ratio. The sleeve drive is to reverse the rear of the mainshaft. A gear train is used to drive the after shaft. The sleeve is mounted on the mainshaft, and the sleeve is driven by a gear which is keyed to the mainshaft. The sleeve is driven by a gear which is keyed to the mainshaft. The sleeve is driven by a gear which is keyed to the mainshaft. The sleeve is driven by a gear which is keyed to the mainshaft.

As an alternative procedure, the sleeveless oil stamp is applied to the cylinder from below and is made removable by the use of oil to separate all interior parts. The oil is coated by dipping the bottom of the stamp and made to penetrate the cylinder wall and make passage for a short distance at the top of the cylinder. After the oil has penetrated, the sleeveless stamping sleeve is applied and the sleeve stamped. Strachan's 1-250 Regulus monofluid of taking many years service. About three quarts of oil is required directly beneath the sleeve indicator is provided in the center with filtering screen, and provision is made

This report, by E. J. Briggs, G. F. Hull and H. L. Dryden, deals with an experimental investigation of the aerodynamic characteristics of a centrifugal high speed pump, made at the Bureau of Standards, and compares the results obtained with the theoretical predictions of the National Advisory Committee for Aeronautics. The investigation was carried jointly by the Bureau of Standards and the Ordnance Department, United States Army, and was made possible through the courtesy of the Lynn Works of the General Electric Co., where a large centrifugal compressor was made available for the purpose.

Left, drag and centre of pressure measurements were made on models of the type used by the Air Service on propeller driven, at speeds ranging from 550 to 1,000 ft./sec. The results show a definite limit to the speed of which airfoil may effectively be used to produce lift, the lift coefficient decreasing and the drag coefficient increasing as the speed approaches the speed of sound.

The change in the lift coefficient is large for high aspect ratio (center ratio 0.14 to 0.20) and for high angles of attack. The change is not marked for low aspect ratios (center ratio 0.18) at low angles of attack, for the speed range employed.

At high speeds the center of pressure moves back toward the trailing edge of the airfoil as the speed increases.

Special Advisory Committee for Assassinations, Washington, D.C.

Preparing the Night Airway

By EARL D. OSBURN

In the fall of 1934 Colonel Henderson announced that there would be a night mail service between New York and Chicago. On May 1, 1935, the routes between Hellef Field and Cleveland were tested out. The first trial flights between those points commenced in May. The route leg between Hellef and Cleveland is not quite so far advanced but trial flights should begin soonest this month. The lighting of the routes between Cleveland and Chicago was started last summer.

The general public considers that eight flying experiments were carried on during the fall of 1933 between Cheyenne and Cheyenne. That part of the route is far the most part over flat or rolling country and was most suitable for what, at the time, was considered a very doubtful experiment. The week of trial flights took eight flights on a regular schedule plus one point to point flight and one point to point lighting flight. During the winter of 1933-1934 the details of the lighting and the establishment of emergency fields were carried out and on July 1, 1934, the Air Mail started its regular night service between Cheyenne and Cheyenne.

Important Routes

The route between New York and Chicago is the most important from the traffic point of view but the difficulties of night flying are very considerable. From the point of view of terrain, Hellef Field is the most difficult route to follow. In the Rockies, the high points being only a mile over 10,000 ft. The country, however, is very much up and down so one part of the course there are seven ranges of hills in a little less than 50 mi. The hills are wooded and steep and the valleys are very rolling with few flat spaces. The greatest obstacles, of course, are the high peaks, as in bad weather the clouds lie on top of the hills.

To fly adequately enough through the country it would seem impossible to find level landing fields at suitable intervals through the Alleghenies. J. B. Whitlock, the superintendent of the Eastern Division, however, has not reckoned through the country as any sacred stool. For three years now he has been working on a night route and has made routes over a distance of 2000 miles and more. The first route is the establishment of night bases. This was the moving of the eastern terminals from Garfield City, L. I., to Hellef Field near New Brunswick, N. J. This not may have saved 50 mi in distance with the same route twice that New York but it started the line and over 100 mi of flat country instead of 50 miles of rocky country to the north. Finally, Whitlock and the police here living the more easterly coast and joining up with the old course of 114 mi. etc.

Miles Difficult

Through the latter country enterprises landing fields are set at about 25 mi intervals and if the plane hits a rock or tree the chances are pretty good that the pilot will find a place to go down in. When down in the hole he must get out as quickly as possible. The country is largely inhabited by the Pennsylvania Dutch and many of them cannot speak English so this language has only recently been taught in the rural schools. The land is leased from the farmers at from \$10 to twelve dollars per acre per year depending on the rate of interest. The rent is payable half yearly and the other half yearly the owners come to collect. Now the field must be smoothed and sometimes dammed. The cutting of trees is also leased property in part of the lease terms, but trees in the approach to the field must be cleared for safety and some of the trees are very precarious. Mr. Whitlock has a great deal of the ground cleared and the trees cut and piled and often set at the edge of most of the trees from Hellef Field to Belknap. In places where concrete has been removed and on one field two tons of dynamite has been used to clear out stumps.

The grading of the fields and the building of the houses for the flying clubs is done by the local contractors, the most notable, however, being in Air Mail personnel, but having three trucks accepted in each.

Caravans

A caravans must be found for each field where duty is to run the bases during the night and to light the landing fields. The drivers are paid a \$25.00 round-trip light which is usually set at a single of 2.5 deg with the lampage and previous at the rate of six cents per minute. The General Manager is now trying to work out a system whereby the season will pass when the bases are thrown along the line of the course. The bases is placed on a 50 ft. windmill tower. The tower is supplied by a Weidler power plant which can

June 1, 1936

AERONAUTICS

unit of a 4 cyl engine driving a generator, but the charge battery system which is used in the western bases has been adopted. The boundary lights are set at intervals of 100 ft. around the field are run by wet batteries and should burn eight nights for six months without change.

The placing of the bases in relation to the field requires quite a bit of thought and in the daytime the light has been placed at a tall pole so that the ground crew can see it so that the pilots should have no difficulty. As more bases have been built at Belknap about 2 mi. from the old field 16 ft. track length and is level with good approaches, though not ideal, it is certainly a great improvement. It will be fitted with a French B.F.T. flood light. The new hangar is completed and as the base is now in operation it promises the most extensive use of the new fields at a great interval.

There is a crew of about ten men at Belknap, exclusive of the radio station, who it is said only takes 20 min. to fuel the plane, inspect it and start the pilot off on the next leg. On the day that the writer was there, however, J. D. Hill came in with a passenger, the first that he had had during the year. He had been flying with the Mail Inspection crew and had a valve in his engine sticked and that cockpit was necessary. It took 15 sec. from the time Hill landed until the time that he was off again. Whitlock's Hill had flown for some 330 mi. above the clouds on his way from Cleveland. When he came down through he was 5 mi. north of Belknap. Recovery should always be given more and more to the pilots and more bases become very proficient. Present development along these lines has only been brought about by cooperation between the instrument makers and the pilots. The pilots who are trying it are constantly doing their share to help along the art of aerial transportation.

The first definite date for the starting of the night service has it probably will be about the first of July. The day service will also be continued requiring a slight increase in the number of pilots.



Bell Photo

Inspecting local construction job seen its building, and such that the conditions and Superintendent Whitlock at a tour of inspection at use of the emergency fields



Bell Photo

Upper left: Bellanca Ranger, the office and the roller doors. Lower left: Inspecting and repairing a plane at Belknap. Right: Biases, wind cranes, power house and boundary light on one of the emergency fields.

On the average the fields are somewhat larger than in the west, the smallest being 30 acres. Most of them are four

June 5, 1925

The Douglas Transport

Description of the Douglas C1 Transport Plane Which Is Being Constructed for the Army

The latest production of the Douglas Company is the Army Transport C1. This plane is designed to carry six passengers and two pilots but can be adapted to carry such loads as a Liberty engine. The design is reminiscent of the World Cruiser and follows conventional lines. This plane was produced in response to a request for bids issued by the Air Service. The wings are constructed

The wings are constructed in a conventional manner. They are all box sections using spruce cap strips with two-ply spruce cover on each side, together with the aeronautics spruce and plywood gussets, stiffeners and fiber blocks. The wing ribs are of the garter type and made of spruce throughout, except for the corner trim gussets which are three-ply aeronautics. The main spars are made of laminated spruce, anchored to laminated fittings, bolted to the spars. The external wing bracing consists of rolled steel strand rods and streamlined dural tube struts. The landing bracing is reinforced, so that the transverse fuselage rails at the wing lower stations may be omitted to provide extra passage through the fuselage.

Cabin

Holding space may be provided for by rearing with a small amount of weight to take care of the longer and extra fittings and panels. The wings consist of seven panels as follows: 3 upper outer sections, 2 upper center section, 2 lower outer sections, 2 lower inner sections. The lower inner sections, which carry the main gear, are streamlined in them, and which have windows built in, are, together with the sole, 3 lower struts, also built.



The Douglas C1 Transport Plane

The construction of the tail surfaces is conventional, the fin and stabilizer being of spruce beams and ribs, and the elevators and rudders of sheet spruce and spruce ribs. The stabilizer is adjustable in the air through the usual means of a hand wheel coupled to a worm and slot at the tail. The rudder is coupled to the stabilizer from 90 degrees with the main plane.

The engine is the conventional duralite axle sole track gear. The struts are streamlined chrome molybdenum steel track bars and the sole of the runs material. The tires are 30 in. x 8 in. straight sole airplane tires on wire wheels. Rubber cord provides the absorbing action. The tail skid is in the single

scissor type, made of heat treated chrome molybdenum steel tubing, and is connected rigidly with the pilot's seat. The tail skid is provided with steering on the ground.

The Douglas is constructed of known military tubing and swaged steel rod. The joints are to be cold-drawn or approved otherwise. The engine section and 1 ft. 6 in. tail section are to be built up in sections. All joints are to be made of dural tube or aluminum tubing. The rear of the fuselage is covered with cotton over furring strips except for the doors, steps, etc.

Fuselage

The engine section, carries the Liberty engine in a nose type radiation, and the engine is to be mounted in front of the engine compartment, three sections. The pilot is given an exit hatch on the side of the fuselage, and the port and wheel type control is provided and the landing gear, fairing, etc., is so arranged that the two passengers may change places in the air. Quick and easy entrance is had from the pilot's cockpit to the passenger compartment.

The passenger compartment has a clear nose section of 46 in. width by 30 in. height. It is about 18 ft. long.

Access from the ground to the compartment is through the side of the fuselage and the other on the right. A single port and wheel type control is provided and the landing gear, fairing, etc., is so arranged that the two passengers may change places in the air. Quick and easy entrance is had from the pilot's cockpit to the passenger compartment.

The passenger compartment has a clear nose section of 46 in. width by 30 in. height. It is about 18 ft. long. Access from the ground to the compartment is through the side of the fuselage and the other on the right. A single port and wheel type control is provided and the landing gear, fairing, etc., is so arranged that the two passengers may change places in the air. Quick and easy entrance is had from the pilot's cockpit to the passenger compartment.

Characteristics

Wing area	500 sq. ft.
Span	60 ft.
Length	36 ft.
Height	10 ft. 6 in.
Weight	1,500 lb.
Empty weight	1,000 lb.
Load capacity	500 lb.
Passenger capacity	6 passengers and pilot
Engines	2 Liberty
Speed per pass. at 7 passengers	140 mph.
Speed per load of 5 passengers	140 mph.
Max. speed	145 mph.
Altitude	8,000 ft.
Rate of climb	400 ft. per min.
Endurance	10 hr.
Range	1,000 miles
Head of loading weight	Varies with wing loading from 12.5 to 16.5 lb. per sq. ft.
Landing speed	65 m.p.h.—max. speed 110 to 120 m.p.h.
Take-off	10,000 to 15,000 ft.

Aviators Meeting

The last meeting of the Aviators Post No. 743 was held in New York City on May 19. Due to the unavoidable absence of the Commander, C. S. Mathews, the Third Vice Commander, Henry H. Lockett, presided. After the transmission of the regular business of the post several members addressed the post on aspects of interest.

Bob Miller was May, Wm. L. Moore of the Second Company, Air Mail Division, presented a report that it was very necessary for the former efficient to hold frequent meetings at the route they held during the war. He said that nominating a reserve commission would not work any hardship as no man is required in the present time. The Major of the Reserve is given a reserve commission to be composed of members of the post. In this connection, a will be presented to the post on the nomination of pilots and officers.

The next speaker was Father O'Flaherty, the popular skipper of the A.E.F. squadron. He described some of his experiences in his rescue trip around the country visiting former pilots. He was followed by Col. Berard E. Felt, who made a plea for commercial aviation. He stated that it is the duty of the post to do all it can to help to build up and increase our air power.

In the point that the telephone was desired by the organization and developed by outside interests and not by us, one could not expect the airline services to do this to the fullest extent.

James of Alabama then gave a resume of his six years of commercial flying and spoke of the present need of expansion of the pilot load and many other subjects of importance. For this reason he has been excepting of a place, we seek him, Sam Brown, homes and boats. He said that he was very old and lame during the industrial depression and had managed to stick and that now he was in quite soft and looked forward to a continued life in peace.

A resolution of confidence in the mother of Lieut. James Jordan, who was killed in an airplane accident, May 17, was passed. The mother, Mrs. Lillian Jordan, is now in poor health, according to Lieutenant Noble of the N.Y.N.G., added that Lieutenant Jordan was flying in the service of his country when killed.

The next meeting of this post will be at Miller Field, 20 during the air meet of the National Guard Squadron. An effort will be made by the members of the squadron to give every one a try.



The Cabin of the Douglas C1

Aviation Graduates Readily Placed

The last few months have shown a surprising activity in aviation, particularly commercial aviation such as the organization of a New York Chapter, air line by some of the principal firms in the country, the engineer, Henry Ford, M. Karp, Charles Dillen, R. H. Scott and others of equal prominence. The effects of this activity is shown in constant expansion at New York University. Since Jan. 5 something over 200 engineers have been received by the Dean of the College of Engineering regarding the courses in Aviation. Requirements are 20 hours of study. These engineers have come from every part of the country, from high school graduates, college students, engineering students, pilots, dentists and others already engaged in aviation. The courses show the deepest interest. Another encouraging evidence of the rapid growth of aviation activities is the ready acceptance of the new courses by the State of New York. The State of New York has recently created a State Commission on Aviation. Thirty-two men from aviation firms, 60 per cent of the men have been provided with suitable posts after graduation. John Bascom will be connected with the Construction Department of the Air Mail. George De Bell will join the Design Department of the Westinghouse Co. at Oakdale, N. Y. John Bascom will be connected with the Government Air Service, with under good openings for other men.

Japanese Flight

The Japanese Charge d'Affaires at Moscow on May 12 telegraphed to Tokio that the Soviet Government has declined to permit the proposed flight of two airplanes through Russia, on the way from Tokio to London, on a flight sponsored by the Asahi, a Tokio newspaper. The minister said the Soviet Government would permit the Japanese aviators to fly only as far as Moscow.

The newspaper has announced plans for the planes to lay off on their flight of about 7,000 m during June in the hope that they may obtain further concessions from the Russian Government after reaching Moscow and be permitted to continue the trip to London.

The Naval Air Battle of the Future

By M. H. MCINTYRE

It is always of interest to read how *Some* writers like the qualities and the use of naval aircraft, and follow their descriptions of the beginning of a war, especially one between the Navy and the Air Force. In a recent article, Mr. Alfred E. W. Eberle, Chief of Naval Operations, has written the *beginning of the aerial-aircraft War*. He has written the correspondence of the *Naval Air Battle of the Future*, as it will be seen in the future over the sea. After reading it, one wonders why the Navy continues above and at such apparently useless "admirals,"—R. R.

We have pointed to the *Air Battle of the World* as the best example of the difficulties of flying over the sea. There are two principal difficulties with the operation in war. Future battles are measured by the time which might arise shortly after the declaration of a war. An early fleet in the endeavor to cut off lines of communication and supplies and resources will necessarily encounter the enemy's fleet. There are two factors which determine the development. These are: (1) the speed of the fleet, (2) the distance between the destroyers and light cruisers and the heavier battleship. The more both will suggest the line. Behind the battle cruiser, the main body will be concentrated on battle

ships; the destroyers and light cruisers will be concentrated on information as to the whereabouts of the enemy. He needs to do everything in his power to get that information and at the same time to plan the attack. This information is to their own losses. So far, we have not necessarily put any planes on the destroyers, but there are two reasons for this: (1) cost, (2) lack of space. For out of the vast numbers of the enemy, a pilot and observer will stand out over the rest of the battle ships and be anticipated all over the sea. Behind the third is a probing right, the pull which makes a role or two in the sea and comes out over the French coast in search of the *U.S.A.* Within a few hours the *U.S.A.* will be behind the *French*. Every bird of the ocean takes flight from safety. With nothing but a damaged torpedo in a glass boat to guide them, they dive on over the treacherous waves.

In sum, that makes a conflict with the ocean, three legs to the human. Two legs are the ships, the last leg is the air. The third consists of our true radio, the last leg of communication. As the observer pounds the key on a trans-*mitter* to get this message through, every combat plane may dive in the water. The pilot will attempt to save safety as much as he can. The radio operator will do the same. He tries this, but the radio operator will not be able to do this, because he is not well informed and upon or shore command. If we find it somewhat difficult to work out elaborate rules out in the spirit of our laws, how much harder task has this young sector with the responsibility for the safety of the nation on his shoulders.

He seeks safety in flight, our pilots start back to shore. She will, we decide, have faced a leaded role as in the actions to carry out her part of the seafaring problem and ship, they are confronted with a definite problem in finding

A striking illustration of what the Navy thinks of the importance of aviation in naval warfare and to what extent it is believed will be given in the accompanying *Hannover* memorandum. In these, the government issues over undertaken by the Australian Navy, 93 surface craft and 34 submarines will be employed while 120 seaplanes will constitute the Air Force, more than the total number of surface and subsurface craft.

Admiral E. W. Eberle, Chief of Naval Operations

As soon as the Navy next expects several hours and miles at sea, aircraft must go on surface ships. The first that feel bad on the part naval battle will be an airplane and then a series of short flights up and down. The last to the sea, the last to approach will be the carrier. The carrier will be the last to approach which need be the final and conclusive approach.

Rear Admiral W. A. McDermott, Chief of the Bureau of Aeronautics

among battle fleet, struggling to make that one pass which one sweepingly launch their bombs. The masses arrive along here, this point as well as they, and as the bombers drive over the great vessels pitching and rolling in the white spray on the passes obscured by the clouds of smoke and fire, the ships will be driven to the deck and made for the observer to do in his strength to drive right in the wind, the speed and mass of the mass. These things he can only guess. At the planes, over their various ports, they will find themselves subjected to a long series of attacks, with many planes and bombs falling. As they catch the ships and drop bombs, these are filled with their eyes the periscope field of their masses. But with the energy, and blinding by a quick turn of the rudder out on the enemy turn aside. To be effective, the bombs must fall in a restricted area, which forces the planes above the carriers in a band broad enough to let them in the path of the carrier. The observer for the observer looks but lets us stay enough at any time.

Associated with the departure of the bombing squadrons, a torpedo plane squadron will make off from another carrier. This squadron will likewise be harassed by the same sort of passes. Under the nose of the carrier, the torpedoes will be driven in, in height. The torpedoes will be dropped from a very low altitude. Above 500 feet the torpedoes are struck off in the fall. Below 100 feet, the weight of the torpedo as it hits the water may split the torpedo tube or even the hull. With the use of the water only fifteen feet back, the torpedo plane has been found to open its tubes and drop them into the hole made by the tube with the hope that the collision may crush the striking plates. Under such conditions, the torpedo plane pilot will be a long way. His observer, armed with dropping the torpedo on the same altitude, will be forced to drop his bombs at the same time. This is a state of constant and uncertain danger.

There is another to consider in another sector. A different problem from that which he encounters is launched, they have had loads which militate against them. Even when fed under favorable conditions, they can not survive, due to the weight, and drop out of the water at a certain point. The larger the load, the greater the speed and thus with some interval. In other words, it is one thing to find glowering potentialities. It is another to deal with an after ship.

LIGHT PLANES AND GLIDERS

Edited by Edmund T. Allen

The Morehouse Light Plane Engine

The Morehouse 8B, an engine completed December last, is now at McCook Field. The tests, which we witnessed personally, were highly encouraging for light plane builders. For we realize that we have at least a real promise, and so one at a reasonable price. The diameter of the 8B is 10 inches, and the engine plane is 100 cubic inches. It has taken 100 cubic inches to get a good engine. The 8B is a reasonably simple, weather plane, rank usage of varied weather conditions, having to operate on solar gas and oil, and not having very frequent overhauls.

The engine is of the two cylinder opposed interrupted type. The engine is simple, it is compact and compact. The cylinder is cast in one piece with no connecting rod. The cylinder is the last away from the valves and head. On the cylinder where it was developing 10 hp there were no overhauls or troubles although the air draft was not as great as we like the case with flying.

The operator of the Morehouse has gone up ample material to the engine and has found it to be a good engine and there are no problems.

The 8B has received special attention at these points of possible trouble, as its ruggedness attests its probable length of life. Those who are apprised in the two cylinder type of engines would see the smoothness of the M-8B as the incomparable. There are very little vibration and the engine is built and constructed not to have any vibration in any manner of the engine cylinder.

The higher speed of operation gives it that "swinging machine" look that is very different from the "panty." We are used to it in small engine planes. The M-8B will lend itself very nicely to streamlined construction. The engine is built to be easily removed from the cockpit to take up the natural curve of the under seating and the oil filter and breather at the top of the engine units fit well with the top seating. The cylinders and engine are kept in the cockpit air stream and they are left uncooled as far as possible. In some cases there has been trouble with the cooling system, but a simple cylinder cooler, such as a valentine, clearly for location. A very poor job of cooling is a two cylinder opposed engine in a light plane may be considered in the *Panard "Trot"* light. Two holes are set in the roofing for the cylinders project through the shape of the nose and provide a large amount of cooling to the engine.

With the arrival of the plane, interest is now at hand. Mr. Morehouse has put a price on these engines that is extremely close to the cost *Sears*. He hopes it is late as possible so as to give as much time as possible for the orders for the season received.

With the arrival of the plane, we will be free during the winter months for the engine.

He compares this engine with others, which are available to the light plane builder, and is struck with the fact that this is the only engine in this country that has successfully passed all of the test we have been through a remarkable one. There are a few others, but they have not been tested in the same manner as this. At the January competition last year, there was not a type that completed the tests without trouble. And so the English engine have been considered very doubtful and as we were expected to Germany for the light planes competition. Their own light plane tests last year were lacking in precision. Through the efforts of the Society, the *French* engine, the *Morehouse*, has been continually the need for a real competition engine in the 80 cu. in. size. At last it has arrived, and we wish it every success.

Gliders Again

The *French* interest in gliders and soaring flight which is being shown in our requests for information, for drawings and

details of a simple glider, marks the annual reawakening of the glider fever. To those who have never flown a glider before, and who appear to be interested in it, it is interesting how many there are who, having never flown, look to the glider rather than to powered craft for the satisfaction of their desire. To those who have flown gliders the temptation comes either as the call of the sport itself. A group of test pilots were recently called upon to test a new landing gear which was to be used in a glider. They found the motion was entirely different from the high pressure automobile, they were used to—and so engrossed did they become in "spinning another gear" that it was presently necessary to call attention to the fact that this was a landing gear test and not a new form of sport to last all day long.

Others are attracted by the desire to fly.

Those who have never flown a glider, and those who have

never heard of the *French* gliders, are asked to do so.

The French have now discovered several gliders within the bounds of France, as well as in their colonies across the Mediterranean where one can now inquire on and with no trouble at all.

One of our engineers presents with the possibilities of similar gliders in our range of hills in eastern Ohio and in western Virginia, where flying over there from Dayton to Washington in fact there was once temptation to come down in the old *BBB* to see if one could discover any remote corners of the *French*. If one could have a *VIII* instead of a *BBB* the stunts would certainly be attempted. And so we may possibly have a far better flying field than the *French* *BBB* of Le Creusot. There is even though its actual soaring speed may be greater because of its greater forward speed in front of the first range of high hills with a strong wind blowing the level ground one could end soaring quite easy.

The *French* interest, of course, has been stimulated by the power of the *French* wings as a glider, for gliders can be built by almost anyone, they cost very little, and they can be flown without a great deal of training.

There are all kinds of planes we still have in France and sport, from the old glider built in *Blois* of solid cloth and wood, to the modern *French* gliders, which are built carefully built, highly efficient and ruggedly built machines of the German Technical Schools. One of the best planes that was built in the United States during the period of the revival of soaring flight in 1922 was the *MIT* glider No. 1. This glider has successfully in France, in competition with the *French* gliders, won the *BBB* changes have been made in the design measurements with our increased knowledge of the factors preventing most efficient gliding flight. The details of the design sufficient to enable anyone to build the glider strong and stable and controllable will be given in subsequent issues of *Aeronautics* as they are recommended. The *BBB* was originally built in *Anchorage* in August of Sept. 4, 1922. It was the result of a glider design competition held by the *Aeronautical Engineering Society* in 1921. The Society built the glider in Cambridge, Mass., in the spring of 1922, testing every important part in the *Farnell Materials Laboratories* of the Massachusetts Institute of Technology. The best gliders were built at *Bethel* located near *Spencer*, Mass., and it was shortly thereafter taken to France to represent this country in the *French Glider Competition*. Up to the time of its accident it was leading in every event and was making a strong bid for the prize.

It flew quite easily, was quite stable and maneuverable and was very easy to handle both in the air and on the ground.



Map by: Schmittner & Co.,
Berlin, 1924.

Dear Sirs:

When the "Fokker VII" left Philippopolis on its Holland flight on June 1st, we were afraid that the wings might have suffered from the heavy conditions, and therefore would have to suffer damage on the latter part of the journey.

We were now most anxious of the health of

the wings. I thought we had only one chance during the long flight that gave sufficient room to stay with the aircraft. In the open during the long flight in Philippopolis. This resulted in the wings being very sorely damaged by wet from plane having to fly over swampy wet land from the sea until the last was to the Balkan. But we experienced continuous rain and heavy rains.

However, we had to pass over-tropical and tropical regions, in which the planes had to withstand very great heat. During the same month, the Fokker VII C. had been exposed to the same weather conditions. To return to Batavia I find the wings were practically in the same condition as when leaving Amsterdam.

However about this circumstance one gradually due to the fact that the wings were finished with Valspar paint.

Yours truly,

Janvier

*Across two continents
—with Valspar!*

FROM Amsterdam to Batavia in the Dutch East Indies—that is the record of the sturdy Fokker VII, piloted by the Dutch aviator Van der Hoop.

A long, grueling run! For 9½ miles this all air liner was buffeted about through all kinds of weather—driving rain storms, snowdrifts, blustering heat of the tropics. And with a forced landing in the middle of the ocean, the Fokker, it seemed in the open for weeks waiting for repairs, exposed to heavy night storms.

Yet at the end of its journey—wings, fuselage, and other vulnerable parts were as good as ever, Valspar paint, of course! For like so many other leading airplane builders, the Fokker Company knows that no other varnish can equal Valspar in service and weatherproof protection.

VALSPAR
Paints • Varnishes • Lacquers



Please write in advertising. Please mention AVIATION

MONUMENTAL AIRCRAFT CO.

Office
1030 N. CALVERT ST.
BALTIMORE, MD.

Warehouse
College Park, Md.



Aerodrome
LOGAN FIELD
MARYLAND

Announcement to all users of aircraft

We announce the arrival of 3 more car loads of J.N. plane and OX motor spares. These complete practically all our previous shortage and we are now better than ever before equipped to serve our growing list of customers. Ask us for what you want.

The large volume of our business enables us to offer these to the public at the most attractive prices. These prices have been widely commented upon. To demonstrate this, see the following extracts from our catalog:

Spokes	2.00	Propeller hub flanges	8.00
Tires, D.H.	8.30	Zodiac, California	81.00
Tires, D.H. (front tire only) per front	3.50	H. H. double adams wings	\$45.00
Front landing gear struts	8.00	Dante Ramps	15
Complete set of 80 propellers	9.00	New Biplane cockpit	\$15.00
Double magazine	9.00	Hornet 15 ft. tailplane	\$7.00
Altimeter	2.00	Tank on biplane struts	\$12.00
Front prop.	2.00	D.H. wheels	8.400
Cylinders	8.00	Complete set 20 h.p.	8.25
Vulcan	8.20		

Genuine one plane canvas T-hangers, brand new, complete, with poles, ropes, pens, etc. Lo.b. Baltimore \$130.00.

PARACHUTES:

About 25 feet radius, complete with ropes and packs, brand new \$30.00.

SPECIAL ITEMS OF INTEREST TO ALL USERS OF AIRCRAFT OX PARTS

Distance Thermometers—government specification, brand new \$7.50. Buy one of these for your engine and know at all times whether it is running too hot or too cold. The satisfaction of owning one of these is worth three or four times its cost.

Exhaust Manifolds for all types of OX \$3.50

Add greatly to the comfort of flying.

Compass, brand new, vertical or horizontal \$10.00

IN PARTS			
Flying or landing wires	\$1.50	Gasoline tank gauge	\$4.00
Tail skid assembly	\$3.00	Control stick	\$2.00
Rudder bar	\$1.50	Re-enforcing tape, 2", cotton, yd. 6c	

We mention here a few of the items in our catalogue. It contains 16 pages of bargains like the above. Send immediately upon request.

"THE LEVIATHAN OF THE AIRCRAFT FIELD"

THE NEW YACKEY LIBERTY-ENGINED TRANSPORT

MOST EFFICIENT TRANSPORT PLANE IN THE WORLD

SELLING FOR LESS THAN \$10,000

Set Up and Test Flown
F.O.B. Forest Park, Ill.

\$6,750.00

Performance

Horizontal high speed, 125 m.p.h. Cruising speed, 100 m.p.h., at 1,450 r.p.m.
Flies 65 m.p.h. at 1,180 r.p.m. Lands loaded at less than 40 m.p.h. Climbs to
16,000 ft., with load of over 1,152 lbs., in 29 min. 30 sec., climbing the first
6,500 ft. in 6 min. 50 sec. Service ceiling 22,000 ft. Handles well at either
high or low speed.

Characteristics

Pay load 1,000 lbs., weight empty 2,390 lbs. Useful load, 1,389 lbs. Gross
weight, 3,770 lbs.
Span 47 ft. Cord 6½ ft. Loading 9.4 lbs. per h.p., 7.2 lbs per sq. ft.

Construction

Duralumin throughout; steel tube fittings. Fusing, Haskelite water-proof glued
veneer, with spruce cap strips. Linen covering treated with Tatamine Ti-two
pigmented aluminum dope. Extra strong fuselage and improved ailerons.

The YACKEY TRANSPORT, constructed of new material and with the latest refinements,
is the result of our four years' experience in the development and operation of the Yackey
Liberty-engined Breguet, whose efficiency and reliability are recognized throughout the aviation
world.

We are increasing our factory capacity to a shop every two weeks to meet the demand for the
YACKEY TRANSPORT—the finest air carrier today at any where near its price.

THE YACKEY TRANSPORT IS BUILT UPON HONOR AND BACKED BY AMPLE
RESOURCES AND SERVICE.

We will gladly send full details and photographs to responsible parties upon request.

YACKEY AIRCRAFT COMPANY
FOREST PARK, ILLINOIS

AIRPLANES FOR SALE

We have 333 airplanes that we must sell this year including Standards, Jennies, Canards,
Orioles, D.H.'s, Spads, T.M. Scouts and others. We have a large number of Standards, Jennies
and Canards set up, test flown ready for immediate fly away delivery. Come and take your pick.

NEW STANDARD J-1 AIRPLANES

with guaranteed overhauled Hispano-Suiza motors, 150 H.P. - - - \$1500.00

NEW STANDARD J-1 AIRPLANES with new OXX6 motors - - - 1300.00

NEW STANDARD J-1 AIRPLANES with Government overhauled OXX6 motors 1100.00

NEW STANDARD J-1 AIRPLANES with new OX5 motors - - - 900.00

NEW STANDARD J-1 AIRPLANES without motor - - - 750.00

These airplanes come complete with tools and instruments and the front seat is built so as to accommodate two passengers. These airplanes have been reconstructed and new longerons, new tailstruts, new wings, new struts, new fittings, new instruments were installed where needed.

LEARN TO FLY

NO BOND REQUIRED FOR
SOLO FLIGHTS AND NO
CHARGE FOR BREAKAGE

\$100⁰⁰

ROOM AND BOARD
NEAR FIELD AT \$10.00
PER WEEK

Special Offer for June, July and August

We will guarantee to teach a student to fly and successfully operate an airplane by himself, regardless of the number of flying hours required, and further, to furnish an airplane, free of charge, for the period of one hour for practice flights.

The flying school of the Robertson Aircraft Corporation is one of the oldest and best known in the United States. All of the instructors are cavalry aviators with wide experience and the equipment is the best that money can buy. The flying field is approximately six miles from the city of St. Louis and is easily accessible by railroad, street car and hard surfaced roads. It is the largest and best privately owned field in the country and the International Air Races of 1923 were held there.

Our course includes thorough flying training as well as complete instruction in the over-haul, care and maintenance of both the airplane and motor. The time within which one can learn to fly, varies with the individual, eight to ten hours of dual instruction, stretched over a period of ten days to two weeks should complete the most stubborn case, and from then on, the refinements of the art can be gained only from experience. Commercial aviation is a rapidly growing industry. Don't delay! Enroll now!

Robertson Aircraft Corporation

St. Louis Flying Field, Anglum, Mo.

Take Advantage of This Offer

Five Dollars Worth for \$4.00

We have left from an edition of 5,000 a few copies of **WHO'S WHO IN AMERICAN AERONAUTICS**. To clear our shelves and make way for the new edition of **WHO'S WHO** which is now in preparation, we will mail, postpaid as long as there surely lasts, a copy of this valuable reference book.

Free with each new subscription to AVIATION

如图所示，某人站在一水平地面上，脚与地面的接触面积为 $2 \times 10^{-2} \text{ m}^2$ 。

While they last.

While this offer lasts you may secure AVIATION for a year (52 issues) at the regular subscription rate and WHO'S WHO IN AMERICAN AERONAUTICS, (the regular price of which to everyone has been \$1.00) for the cost of a subscription alone.

Who's Who contains nearly a thousand biographies of those prominent in American Aviation, hundreds of photographs, valuable statistical information, organization and directory of the Army Air Service, Bureau of Aeronautics, Navy Department, Air Mail Service and other important organizations.

AVIATION is the only American publication which gives each week a review of the important news of aeromotors throughout the world, photographs and descriptions of the latest machines and cautions on the problems and progress of flying in the United States.

You need AVIATION to keep in touch with big new developments this year, and you will find WHO'S WHO a valuable supplement to your reading.

The *average* of many trials has been found to only about 100 new photons.

So Send In The Cannon Now

GARDNER PUBLISHING CO
225 Fourth Avenue, New York

For the enclosed \$10.00 U.S. dollars (\$4.00 in U.S., \$5.00 in Mexico and Canada, other foreign, \$6.00) send me postpaid a copy of Who's Who in American Aeromotors and the next 52 issues of AVIATION, as accordance with your special offer.



ONLY A NIGHT'S FLIGHT

NIGHT flight mail service between New York and Chicago will be in operation July 1st. Mails dispatched from each city about 8 o'clock in the evening will be delivered on the first mail delivery the next morning in the city at the other end of the line.

As far as mail service is concerned it brings New York and Chicago as close together as Minneapolis and St. Paul, as Chicago and Evanston or Brooklyn and the Bronx.

The service will have the effect of saving a business day between the Atlantic seaboard and the metropolis of the middle west. Preliminary surveys indicate that from two to seven planes will have to be used in each direction, each ought to handle the mail

Our return to the Air Mail Program is a change of which we were told a great satisfaction could be derived.

STANDARD OIL COMPANY

(ENCLASADA)

卷之三

General Offices 910 S. Michigan Avenue
 INDIANA 8-1000 A 8 DADDY
 Indianapolis Des Moines
 South Bend Sioux City
KANSAS Kansas City
 Wichita
 (INDIANA)

CHICAGO, ILLINOIS

NAME	MANUFACTURER	MANUFACTURER
Fisher	Duluth	St. Paul
Hillman	Minneapolis	St. Paul
WESCOOREEN	Minneapolis	St. Paul

SPEED WITH SAFETY



IN 1924 THE
CURTISS EXHIBITION COMPANY

Flew over 100,000 Miles
Carried over 3,500 Passengers
Trained 52 Student Pilots

WITHOUT ACCIDENT

THIS RECORD WAS MADE POSSIBLE BECAUSE OF
Good Equipment, Competent Personnel, Careful Inspection

Among our satisfied clients are:

New York Times, New York Tribune, New York World, New York American, New York Evening Graphic, Boston Post, P. & A. Photos, International News Reel, United News Pictures, N. E. A. Service, Wide World Photos, Pathé News, Fox News, Famous Players, Fairchild Aerial Camera Corp., Underwood and Underwood, Hamilton Maxwell, Inc.

We are offering our 10 hour flying course
for 1925 at greatly reduced rates.

Write for Booklet

CURTISS EXHIBITION COMPANY
GARDEN CITY, N. Y., DRAWER B.